

Future-proof your processes

Want your team to work faster without compromising on quality? You don't need to create yet another 'time management' training course. There's a much smarter way to boost productivity in the 2020s. Introducing the IM C530FB and IM C530F — the high-speed, compact, all-in-one line of devices that do all of the heavy 'lifting' for you, as quick as a flash. This means your team can focus on the areas and tasks that enable them to get their work done...instead of having to wait for that 87-page report to get printed without a paper jam...

Our new A4 colour devices are specifically designed to boost your team's productivity efficiently and effectively. IM C530FB (base model) and IM C530F (finisher model) optimize digital workflows with apps and solutions available in the cloud. As a result, all of your processes can work seamlessly, without costly interruptions or waiting times.

- Work faster: Seamlessly print up to 53 pages per minute, cut waiting times and boost productivity.
- Optimize digital workflows: Share and instantly use all types of information, thanks to the MFP cloud connection.
- Scale up at your own pace: Easily customize, manage and add new features to your device, using the new 7" touchscreen control panel.
- Save space: IM C530FB and IM C530F are compact devices designed to take up less space and leave more room for your pressing needs.
- Seamlessly print documents: Print up to 3,250 sheets without interruption and make light work of printing tasks.
- Save time: With IM C530F you work more efficiently by automating manual tasks, such as separating or stapling files together, thanks to the standard finishing function.
- Intuitive and fast operation: The 7" smart operation panel provides consistent operability across multiple devices in our portfolio.
 Simply follow the steps on screen.

Think of all of the things you can do in a matter of seconds on your smartphone. Now imagine what your team could achieve with IM C530FB and IM C530F, the high-speed all-in-one printers designed to significantly optimize your workflows and scale up productivity.

Optimize your workflows and boost productivity with minimum hassle

High speed A4 colour printing

The IM C530FB and IM C530F, with its standard finishing function, have the capacity to seamlessly print up to 53 pages per minute and deliver up to 3,250 pages without compromising quality, thanks to the new large capacity tray. The UI provides consistent operability across multiple devices in our portfolio, so once you manage one device, you can effortlessly use any of them.



Fully digitalized workflows = flawless processes

Today's fast-paced working environment dictates that you always stay connected and meet expectations as quickly as possible.

The IM C530FB and IM C530F give you an advantage in this digital era, with easy-to-use workflow apps that connect your printer to your preferred third-party cloud services. What's more, the IM C530FB and IM C530F also restrict access to print output to the document owners only, thanks to the exclusive Streamline NX Secure Release feature. This gives you total control over who gets access to documents, whether they're members of your team or clients.

Future-proof technology to spearhead your business growth

There's no need to keep updating your devices to get access to new features and functionalities.

With our Always Current Technology, you'll instantly receive the latest updates and always stay one step ahead. IM C530FB and IM C530F allow new software features, applications and upgrades to be downloaded and installed directly to your device on request. This way, the everchanging needs of your business are promptly met. You'll never have to sit and wait for new functionalities to keep up with your business plans. Now you can easily future-proof your company's growth.



Product configuration

Internal Finisher SR1020 (for IM C530F only)

Stack capacity: 500 sheets Staple capacity: 50 sheets Dimensions: 450.8 × 477.6 × 248 mm Weight: 7 kg

Mainframe

IM C530F



7" Smart Operation Panel 100-sheet SPDF 550-sheet input tray 150-sheet bypass tray 500-sheet output tray Weight: 42 kg Dimensions: 470 x 502.8x 843.7 mm

IM C530FB



7" Smart Operation Panel 100-sheet SPDF 550-sheet input tray 150-sheet bypass tray 400-sheet output tray Weight: 38 kg Dimensions: 470 x 502.8 x 643.7 mm

Minimum space requirements Front: 514 mm Left: 100 mm Right: 350 mm Rear: 305 mm Top: 234 mm

Capacity: 550 sheets Dimensions: 420 x 464.5 x 123 mm Weight: 6.5 kg

Paper Feed Unit PB1180



LCT PB1190

Capacity: 2,000 sheets Dimensions: 724.2 x 772.1 x 459 mm Weight: 32.4 kg

Other options

- IEEE 80.2.1 Interface Unit Type M43
 NFC Card Reader Type M43
 NFC Card Reader Type M43
 Unicode Font Package for SAP 1 Licence
 Unicode Font Package for SAP 1 Licence
 Counter Interface Type M12
 Medium Cabinet 76
 Low Cabinet 75
 Caster Table 74

Dimensions are stated in width x depth x height (W x D x H)



IM C530FB/IM C530F

MAIN SPECIFICATIONS

GENERAL	IM C530FB	IM C530F	
Configuration	Desktop		
Printing process	Dry –two component electro-p	photographic printing	
Development	Non magnetism, single component development		
Technology	Electro photographic printing system with laser beam		
Warm-up time	39 seconds		
First output speed: B/W	4 seconds		
First output speed: full colour	4 Seconds		
Continuous output speed			
	53 ppm		
Memory: standard	2 GB		
Memory: maximum	2 GB		
Storage	eMMC: 32GB		
SPDF capacity	100 sheets		
Duty cycle	150,000		
Duplex	Yes		
Weight	38 kg	42 kg	
Dimensions: W x D x H	470 x 502.8 x 643.7 mm	470 x 502.8 x 843.7 mm	
Power source	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz	
COPIER			
First copy speed	BW: 6.5 seconds, Colour: 6.6 seconds		
Multiple copying	Up to 999 copies		
Resolution	1,200 x 1,200 dpi		
Colour mode setting	Default: Black and v	white mode	
	Auto Colour Select	ion (ACS)	
	Full colour		
	Black and w		
	Single colou		
Reproduction ratio	400%, 200%, 155%, 141%, 129%, 122%, 121%, 115%, 100%, 9		
Maximum original size	Book: A3, DL		
-	ADF: A3, DL7		
Zoom	From 25% to 400% i	n 1% steps	
Paper selection	1st tray		
	2nd tray 3rd tray (with pap	er hank)	
	4th tray (with pap	,	
	Bypass tra		
	LCT	,	
PRINTER			
CPU	Cortex-A53 1.2	2 GHz	
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulation	on), PDF direct (emulation)	
Print resolution: maximum	1,200 x 1,200) dpi	
Print resolution	PCL5c: 300 dpi,	600 dpi	
	PCL6: 600 dpi, 1	,200 dpi	
	PS3: 600 dpi, 1,	200 dpi	
Interface	Standard: Mainframe (Ethernet (1000BASE-T/100BASE-TX/10BASE-	-T), USB2.0, USB Host 2.0 (3G Dongle only), Fax), Bluetooth	
	4.2, SD card slot (1Slot/Support SDHC memory card), USB host (Type	pe A:1Port/Support USB flash memory), Optional USB host	
	(TypeA:1Port/Support keyboard), Optional USB host (Type Mini B		
	expansion of ROM storage of the operation unit, Wireless LAN (IEEE		
	Forum Type2 Tag (
	Option: Wireless LAN (IEE		
Mobile printing capability	Apple AirPrint, Mopria®, Google Cloud Prin		
Windows® environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 200		
	Windows® Serve		
Mac OS environments	Macintosh 8.6 or later (
LINIX environments	Macintosh OS X v10		
UNIX environments	UNIX Sun® Solaris (9), HP-UX (11.x, 11i v2, 11i v3), SCO OpenServe (V6.1, V7.1, V7.2), Citrix Xen		
SAD® environmente	, , , , ,		
SAP® environments	SAP® R/3®, SAF		
Network/operating system	PCL5c: Windows 7 (32/64bit), Windows 8.1 (32/64bit), Windows 10		
	Server 2016, Server 2012/R2 (64bit), SAP R/3, SAP S/4, Unix Sun S PCL6: Windows 7 (32/64bit), Server 2008 (32/64bit), Server 2008 F		
	Vindows 7 (32/64bit), Server 2006 (32/64bit), Server 2006 Windows 10 (32/64bit)		
	PS3: Windows 7 (32/64bit), Server 2008 (32/64bit), Server 2008R		
	Windows 10 (32/64bit), Server 2016, Unix Sun Solaris, HF		
	,, , , , , , , , , , , , , , , , , , , ,	, , , , , , , , , , , , , , , , , , , ,	

IM C530FB/IM C530F

MAIN SPECIFICATIONS

SCANNER	IM C530FB	IM C530F
CIS		
Scanning: full colour	46 ipm (simplex)/52	
Scanning speed: SPDF	Simplex: BW (46 ipm (A4, 200dpi)),	
Resolution: maximum	Duplex: BW (71 ipm (A4, 200dpi)), Colour (52 ipm (A4, 200dpi)) 600 dpi 600 dpi	
Resolution: standard	Standard: 100 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi Default: 200 dpi	
Compression method	BW: TIFF (MH, MR, MMR, JBIG2), Grayscale, Colour: JPEG Single Page TIFF (Compression on, Compression off), Single page JPEG (Compression on), Single page PDF (Compression on Compression off), Single page High compression PDF (Compression on), Single page PDF/A (Compression on, Compression off Multi page TIFF (Compression on, Compression off), Multi page PDF (Compression on, Compression off), Multi page High compression PDF (Compression on), Multi page PDF/A (Compression on, Compression off)	
File formats		
Scan modes	E-mail, Folder, USB, SD Card	
Scan area: main scan	215.9 m	m
Scan area: sub scan	SPDF (405.6 m	m), Book
Network TWAIN :	OS: Server2008(32bit)/7(32bit)/8.1(32bit)/10(32bit), Server2008(64bit)/7(64bit)/8.1(64bit)/Server2018(2(64bit)/Server2012(64bit)/Server2012(64bit)/Server2016(64bit)/Server201	
Scan mode (B/W)	BW Text/Line Art, BW Text, BW Text/P	
Scan mode (colour)	Full Color Text/Photo, Full Color Glo	•
Image density	Automatic/Manual: Yes (ad	•
SADF/batch mode	Yes	. ,
Search method of email address	Name, E-mail	address
in HDD		
FAX	POTAL D	av.
Circuit Transmission speed	PSTN, PI G3: approximately 3 seconds (200 x 100 dpi, JBIG,	
Modem speed: maximum	33.6 Kbp	
Resolution: standard	8x3.85 line/mm, 2	
	8x7.7 line/mm, 20	00x200 dpi
Compression method	MH, MR, N	IMR
Scanning speed	46 spm	
Page memory size	Standard: 9.	
SAF memory size	Standard: 4 MB (approximately 320 pages)	
SID code (sender ID) Programming by OMR	Yes No	
Telephone specifications	Handset/tele	nhone
	Monitor speaker On hook dial Tone transmission Pause Pulse/tone selection Reception mode selection Auto answer delay time Busy tone detection	
PAPER HANDLING		
Recommended paper size	Standard paper tray(s): (A4, A5, A6, B4, B5, B6, Legal, Letter, Half Letter, Executive, Foolscap, Monarch, C5, DL Env), Optional paper tray(s): (A4, A5, A6, B4, B5, B6, Legal, Letter, Half Letter, Executive, Foolscap, Envelopes), LCT: (A4), Bypass tray: (A4, A5, A6, B4, B5, B6, Legal, Letter, Half Letter, Executive, Foolscap, Monarch, C5, C6, DL Env, Custom Size paper)	
Paper input: standard	550 shee	
Paper input: bypass	150 sheets	
Paper input: option	Paper bank unit: 550 sheets LCT: 2,000 sheets	
Paper input: maximum	3,250 she	
Paper output: standard	400 sheets	500 sheets
	60 - 220 g	-
	60-176 g 60 - 220 g	m² ²
Paper weight Optional tray(s):		
Paper weight Optional tray(s): Paper weight Optional tray	60 - 176 g	m² m²
Paper weight Optional tray(s): Paper weight Optional tray (LCT): Paper weight Bypass:		
Paper weight Optional tray(s): Paper weight Optional tray (LCT): Paper weight Bypass: Paper weight Duplex:	60 - 176 g	m² m²
Paper weight Bypass: Paper weight Duplex:		m² m² ope, Coated paper, Middle thick paper, Thick paper 1, Thick
Paper weight Optional tray(s):	60 - 176 g Plain paper, Recycled paper, Special paper 1-3, Letterhead, Envel	m² m² ope, Coated paper, Middle thick paper, Thick paper 1, Thick
Paper weight Optional tray(s): Paper weight Optional tray (LCT): Paper weight Bypass: Paper weight Duplex: Paper types Authentication Windows authentication	60 - 176 g Plain paper, Recycled paper, Special paper 1-3, Letterhead, Envel	m² m² ope, Coated paper, Middle thick paper, Thick paper 1, Thick ?
Paper weight Optional tray(s): Paper weight Optional tray (LCT): Paper weight Bypass: Paper weight Duplex: Paper types	60 - 176 g Plain paper, Recycled paper, Special paper 1-3, Letterhead, Envel paper 2	m² m² ope, Coated paper, Middle thick paper, Thick paper 1, Thick ?
Paper weight Optional tray(s): Paper weight Optional tray (LCT): Paper weight Bypass: Paper weight Duplex: Paper types Authentication Windows authentication LDAP authentication	60 - 176 g Plain paper, Recycled paper, Special paper 1-3, Letterhead, Envel paper 2	m² m² ope, Coated paper, Middle thick paper, Thick paper 1, Thick 2 s (Yes) SL/TLS, Transport Layer Security (TLS), Wireless Lan(WEP),

IM C530FB/IM C530F

MAIN SPECIFICATIONS

IM C530FB IM C530F

ECOLOGY

Power consumption: max.
Power consumption operation:
B/W

Power consumption operation:
633 W

Full colour
Power consumption: ready
Power consumption: sleep
TEC*

Sound power level: Standby/energy saving (30 dB/30 4 dB) Printing (dB) Conving (Nominal value)

Sound power level: Standby/energy saving (30 dB/30.4 dB), Printing (dB), Copying (Nominal value)
Sound pressure level: Standby/energy saving (dB), Printing (dB)

Safety regulations

Environmental standard: BAM, Canada Eco logo

Usage and durability ratings

APV: maximum: 10,000 prints

Duty: 120,000 prints

Estimated life: 5 years or 600,000 output

* It is a reference value based on the ENERGY STAR Ver.3.0 test method.

OUTPUT TRAYS AND FINISHER OPTIONS

4x 550-sheet paper tray

Paper size: (A4, A5, B5), Paper weight: (60-220 g/m²)

2,000-sheet Large capacity tray

Paper size: (A4, LT), Paper weight: (60-176 g/m²)

OTHER OPTIONS

Caster table, IEEE 802.11 a/g/n, NFC card reader, Paperlock

CONSUMABLES

5% coverage on A4

Starter toner Black: 7.500 prints Cyan: 4,500 prints Magenta: 4,500 prints Yellow: 4,500 prints Toner (black) 20,500 prints Toner: cvan/magenta/vellow 18,000 prints Photo conductor/developer unit Black: 60,000 sheets Cyan/magenta/yellow: 60,000 sheets Fusing unit 240 000 sheets Waste toner bottle 30,000 sheets Consumable yield based on 3p/j

Ricoh International B.V.

Prof. W.H. Keesomlaan 1 1183 DJ Amstelveen The Netherlands



+31 (0)20 5474111













